

6. Specification for the number of nails to be used per tile (as in Table 1) is based on cyclic testing carried out by the Cyclone Testing Station, James Cook University Report No TS 537

From this Test Report the following maximum allowable pressures are presented in Table 2

Table 2: Maximum allowable pressure (permissible stress design)

No of Nails per Tile	Maximum allowable pressure (kPa)	Equivalent ultimate design pressure (kPa)
7	4.50	6.75

TILE NAILING DETAILS

Nails used on all Savanna Steel Shingle Roofing Systems should be 50mm x 2.8 mm flathead nails, galvanised and painted. Nailing details are shown in Figures 3 and 4. 7 nails per tile are required, nail every module. Begin nailing at the overlap end (as shown tile B, Figure 3).





Figure 3



7 fixings per sheet as shown (generally equally spaced)

Figure 4

GENERAL NOTE :

1. Live load on roof, including persons walking on roof, must only be applied directly over the roof batten
2. All nail positions should be in the same relationship to tile module shape and batten location as shown in Figures 3 and 4
3. For general installation instructions, refer to the Savanna Steel Shingle Roofing Installation Details, available from Tasman Roofing Australia Pty. Ltd.



000467504
Hughes Trueman Reinhold
 Consulting Engineers Planners & Managers
 A.C.N. 003 330 783

[Signature] 15/3/2009
 C.S. PASCOE BE. FIE(Aust).



The Association of Consulting Engineers Australia

6th Floor, TGC Centre
 Mitchell Street,
 DARWIN NT 0800
 GPO Box 4083 PH: (08) 8981 7500
 DARWIN NT 0801 FAX: (08) 8941 1862
 EMAIL: htrdarwn@topend.com.au

SAVANNA STEEL SHINGLE ROOFING SYSTEM
 for fixing to timber battens

Tasman Roofing Australia Pty. Limited
 ACN 081 835 092

DESIGN DATA SHEET
 APPROVED DATE DRAWING NUMBER.

M/102/9
 Andl
 -