



NOTES:

1. ITEM 11. MUST HAVE 30 mm MINIMUM PENETRATION INTO BATTEN.
2. THE CENTRAL SPREADER FIXING SCREW MAYBE DELETED FOR THE 160 LITRE MODEL.
3. ITEM 12. TO BE SUPPLIED BY THE BUILDER OR INSTALLER.
4. BATTENS AND THEIR FIXINGS MUST BE DESIGNED FOR WIND LOAD FOR THE TERRAIN CATEGORY APPLICABLE TO THE BUILDING, AND FOR DEAD & LIVE LOAD. MAX. RAFTER SPACING 900 mm.
5. TOTAL WEIGHT :

160 LITRE 250 kg
 300 LITRE 500 kg

6. DESIGN CRITERIA:

TERRAIN CATEGORY 2.
 MAXIMUM HEIGHT 10 metres
 CYCLONE FACTOR 1.15

Colless & O'Neill
 Consulting Engineers Pty Ltd

84, Woods Street, Darwin, N.T.
 Phone (089) 819644



FLAT ROOF STAND FOR
 RHEEM HILINE WATER HEATERS

DESIGN DATA SHEET

CERTIFIED

DATE 6 JUNE 1986

DARWIN CYCLONE AREA

APP'D. *J.R. Sanders M.E. (Aust)* DATE 8/7/86

DWG.No.

M/501 / 7