

CORRUGATED - SPAN TABLES

(10 FASTENERS PER SHEET)

CORRUGATED 0.42 bmt (0.47tct)-10 cyclone caps per sheet			BUILDINGS UP TO 5m HIGH			
TERRAIN CATEGORY	ROOF AREA	PRESSURE kPa	MAXIMUM SPANS (mm)		MAXIMUM OVERHANG (mm)	
			EQUAL CONTINUOUS	REDUCED END CONTINUOUS	STIFFENED*	UNSTIFFENED*
CAT 1 & 2	D	3.34	1000	1200/950	250	100
	F	4.49	900	1050/850	225	100
	G	5.63	825	975/775	200	100
CAT 2 1/2	D	2.83	1050	1200/950	250	100
	F	3.80	950	1150/900	250	100
	G	4.77	875	1050/850	200	100

CORRUGATED 0.42 bmt (0.47tct)-10 cyclone caps per sheet			BUILDINGS UP TO 10m HIGH			
TERRAIN CATEGORY	ROOF AREA	PRESSURE kPa	MAXIMUM SPANS (mm)		MAXIMUM OVERHANG (mm)	
			EQUAL CONTINUOUS	REDUCED END CONTINUOUS	STIFFENED*	UNSTIFFENED*
CAT 1 & 2	D	3.71	975	1200/950	250	100
	F	4.97	875	1050/750	200	100
	G	6.24	775	925/750	175	75
CAT 2 1/2	D	3.31	1000	1200/950	250	100
	F	4.40	900	1100/875	225	100
	G	5.57	825	975/775	200	100

* Unstiffened/stiffened refers to whether or not the edge of the sheeting has been stiffened by a gutter system or similar. Minimum overhang is 50mm but 100mm is desirable.

GENERAL NOTES:

Working pressures have been calculated in accordance with AS1170.2 (1989). Spans are based on the most conservative combinations of the following factors:-

Basic Wind Speed (V_p) = 57 m/s

Terrain Category Multiplier

T.C. 1&2 up to 5m ($M_{z,cat}$) = 0.95

T.C. 2 1/2 up to 5m ($M_{z,cat}$) = 0.88

T.C. 1&2 up to 10m ($M_{z,cat}$) = 1.00

T.C. 2 1/2 up to 10m ($M_{z,cat}$) = 0.95

Multipliers for shielding, topography and importance = 1.00

External Pressure Coefficient ($C_{p,e}$) = -1.3

Local Pressure Factors (K_1) = 2.0 or 1.5 or 1.0

Internal Pressure Coefficient ($C_{p,i}$) = +0.6

ROOF AREA G refers to any part of the roof within 0.5a of the edge (and ridge for roof slopes greater than 10°). ROOF AREA F refers to any part of the roof within 1.0a of the edge (and ridge for slopes greater than 10°). ROOF AREA D refers to roof areas other than F or G. Where a is the least value of 0.2 building width, 0.2 building depth or building ridge height.

MANUFACTURER:

STRAMIT INDUSTRIES

74 McMINN STREET
DARWIN, NT 0800

PHONE No. (089) 81 2219

FIXING OF

CORRUGATED

IN THE DARWIN AREA

DESIGN DATA SHEET

CERTIFIED:

[Signature]
M.I.E. (Aust)
195063

NORTHERN TERRITORY
DEPARTMENT OF LANDS AND HOUSING

DRAWING No.

APPROVED:
DATE:

[Signature]
29/5/92

M/103/7

DATE:

30/3/92