

M12 GALVINIZED THREADED ROD.  
 PROVIDE WASHERS AT EACH NUT  
 PRE DRILL TIMBER Ø12 ONLY  
 NOTE: ROD LENGTH TO SUIT ROOF.

125 x 25 x 1.2  
 SCREW FIX TO 3 TRUSSES  
 OR RAFTERS WITH 2 x  
 No. 14 TEK SCREWS.


2 x 25 x 1.2 G.I STRAPS  
 3 NAILS PER LEG

100 x 50 HWD. BATTEN CONTINUOUS  
 AND SECURED TO EACH TRUSS.  
 (CONTINUOUS OVER A MINIMUM  
 OF 3 TRUSSES.)

175  
 max

WARNING  
 Product Approval Withdrawn  
 April 2012

ALTERNATIVE FIXING DETAIL FOR  
 CLEAR OF ROOF INSTALLATION

APPROVED FOR INCLUSION IN THE N.T. DEEMED TO COMPLY BY BAC 

DATE 24/12/97

**EDWARDS** MANUFACTURING PTY. LTD.

109 VULCAN ROAD, CANNING VALE, WESTERN AUSTRALIA 6155 .  
 PH: (08) 9455 1999 FAX: (08) 9455 1201

ALL INTELLECTUAL PROPERTY IN THIS DESIGN INCLUDING  
 ANY PATENT, PATENT APPLICATION AND/OR DESIGN  
 REGISTRATION AND/OR COPYRIGHT ARE THE PROPERTY  
 OF A.C. EDWARDS PTY LTD. A.C.N. 008 676 613

CYCLONE FRAME FIXING – WITH PITCH ROOFS

DESIGN DATA SHEET

COLLESS AND O'NEILL PTY LTD  
 CONSULTING CIVIL AND STRUCTURAL ENGINEERS

84 Woods Street, DARWIN, N.T. 0800  
 Ph (08) 8981 9644 ACN 009 622 968

DARWIN CYCLONE AREA

APP'D.: 

OUR REFERENCE  
 4960

DRAWING No.:

m/sid/a

CERTIFIED:  DATE: 12/12/97

DATE: 18. 12. 97