



* NOT REQUIRED WHEN FRAME ECCENTRICITY $X < 60\text{mm}$

LEGEND

- | | |
|---|--|
| <ol style="list-style-type: none"> 1. STORAGE CYLINDER 440 OR 330 LITRES 2. HEAT COLLECTOR PANELS 3. TANK CLAMP (33-0872) 4. COLLECTOR TOP RAIL (33-1941) 5. COLLECTOR BOTTOM CLAMP (34 4120) 6. COLLECTOR BOTTOM RAIL (33-1942) 7. 104x27x2.0 TOP HAT (33-1943) 8. 75x50 HW OR DTC APPROVED STEEL BATTEN * 9. SUPPLEMENTARY 75x50 HW BATTEN OR 75x50x1.6 RHS FOR STEEL BATTENS WITH NO. 14 TEKS BATTEN TO RHS AT 200 CTRS. 10. 40x40x3 M.S. ANGLE TOP CHORD (33-0858) 11. 40x40x3 M.S. ANGLE BOTTOM CHORD (33-6805) 12. 40x40x3 M.S. ANGLE UPRIGHT (33-6803) | <ol style="list-style-type: none"> 13. 40x40x3 M.S. ANGLE UPRIGHT (33-1105) 14. 25x25x3 M.S. ANGLE CHORD (33-1111) 15. 25x25x3 M.S. ANGLE CHORD (33-1110) * 16. No. 14 TYPE 17 TEKS @ 250 CTRS TO U/S EXISTING HW BATTENS. 17. No. 14 TYPE 17 x 55 TEKS TO H.W. ROOF BATTENS OR M8 BOLTS WITH 20x3 WASHERS TO STEEL BATTENS 18. M8 BOLT WITH 3mm WASHERS 19. M8 BOLT WITH 3mm WASHERS 20. M8 BOLT WITH 3mm WASHERS 21. M8 BOLT WITH 3mm WASHERS 22. M8 BOLT WITH 3mm WASHERS 23. 25x1.2 GALVANISED BATTEN STRAP WITH 3 NAILS PER LEG EACH SIDE OF RAFTER FIXED PER DTC M/602/2. ALSO APPLIES FOR STEEL BATTENS. |
|---|--|



Brown & Root

Brown & Root Services
Asia Pacific Pty Ltd
ACN 007 680 317
a Halliburton company

SOLAHART 330/440 L LOW PITCH FRAME

Solahart
Lot 2030 Mackagon Road, Berrimah
Contact Numbers: Phone (08) 8947 0274 Fax (08) 89 471 944

DESIGN DATA SHEET

Certified:

Date: 20-12-01

DARWIN CYCLONE AREA

Dwg. No.

Adopted by the Building Advisory Committee:

Date: 3/5/2002

Approved:

Date: 4-2-02

M/5.11/1