

FASTENERS

THE FOLLOWING FASTENERS, OR THEIR APPROVED EQUIVALENT, ARE RECOMMENDED FOR USE WITH HANDFORD PANELDEK, HANDEK AND CORRUGATED SHEET TO ACHIEVE PUBLISHED PERFORMANCE DATA.

PANELDEK 200		– RECOMMENDED FASTENINGS
Steel purlins. (1.6mm to 3.2mm thick)		No. 10 x 16mm Wafer Head Type 17 screw.
Hardwood purlins (J3 stress grade and over)		No. 10 x 25mm Wafer Head Type 17 screw or Handford Nail (3.75mm x 40mm Annular Thread)
Softwood purlins (below J3 stress grade)		No. 10 x 45mm Wafer Head Type 17 screw

HANDEK 760 – RECOMMENDED FASTENERS (CYCLONIC FIXING)		
CREST FIXING	STEEL 1.2–5mm STEEL 5–6.5mm Hardwood Softwood	No. 14 x 50mm Hex Head + Neo “spaced” Tek screw No. 14 x 45mm Hex Head + Neo Tek screw No. 14 x 65mm Hex Head + Neo, Type 17 screw No. 14 x 75mm Hex Head + Neo, Type 17 screw
SIDE LAPS – “BUILDEX” SCREW, TYPE S POINT No. 8 x 12mm Hex Head + Neo.		

HANDFORD CORRUGATED – RECOMMENDED FASTENERS (CYCLONIC FIXING)		
CREST FIXING	STEEL 1.2–5mm STEEL 5–6.5mm Hardwood Softwood	No. 14 x 42mm Hex Head + Neo “spaced” Tek screw No. 14 x 40mm Hex Head + Neo Tek screw No. 14 x 50mm Hex Head + Neo Type 17 screw No. 14 x 65mm Hex Head + Neo Type 17 screw
SIDE LAPS – “BUILDEX” SCREW, TYPE S POINT No. 8 x 12mm Hex Head + Neo.		

Enquiries and further information available from: HANDFORD INDUSTRIES DARWIN (089) 81 228
HANDFORD INDUSTRIES BRISBANE (07) 265 2999

DESIGN DATA SHEET Northern Territory Cyclonic Areas

Manufacturer:
HANDFORD INDUSTRIES PTY. LTD.
Phone No. 265 0443
Address:
19 PRITCHARD ROAD, VIRGINIA,
BRISBANE, Q. P.O. BOX 157 NUNDAH, 4012.
Certified *Paul J. Handford* MIE (Aust)
Date *11/10/82*

Subject: Fixing, in the Darwin area of
RECOMMENDED FASTENERS:
To be used with Handford Products.
Approved *J. Handford*
Date *19 August 1982*
ISSUE 2.

DRG No. M/103/17