

SPECIFICATION

SPEED DECK (mark III)

ROOFING Roofing shall be Stramit Speed Deck (mark III), cold roll-formed from.....mm. (total coated thickness) steel in continuous strip form having a galvanised coating of class Z430

The trays shall have a nominal side cover of 508mm comprising three rib projections each with an overall height of 45mm.

Each tray shall be fixed at each rib and the purlin spacings shall not exceed..... mm.

FIXING CLIPS Fixing of the roofing shall be by positive locking Speed Deck (mark III) Fixing Clips as supplied by the manufacturer.

FASTENERS Each clip shall be securely fixed to the purlin with..... No..... in the holes provided

GENERAL All fixing shall be strictly in accordance with the manufacturers recommendations as shown on drawings Nos M. 109.7
M. 109.8
M. 109.9
M. 109.10

This space left blank for inclusion of information appropriate for a particular house specification.

WARNING
Product Approval Withdrawn
May 2009

<p>HOUSE DETAILS</p> <p>OWNER</p> <p>LOT No</p> <p>STREET</p> <p>DISTRICT</p> <p>TERRAIN CATEGORY</p> <p>MULTIPLIER</p>	<p>FIXING OF</p> <p>STRAMIT "SPEED DECK" ROOFING</p> <p>IN THE DARWIN AREA</p>	
<p>SPECIFICATION SHEET</p>		
<p>NORTHERN TERRITORY CYCLONIC AREAS</p>		
<p>Accptd. <i>[Signature]</i></p>	<p>DATE <i>11/6/08</i></p>	<p>DRAWING No M/109/6</p>