



NOTES:

- ALL WORK MUST BE UNDERTAKEN IN ACCORDANCE WITH THE STANDARD SPECIFICATION FOR SUBDIVISIONS ALONG WITH PROJECT SPECIFIC AMENDMENTS.
- ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE.
- ALL LINEMARKINGS AND SIGNAGE MUST COMPLY WITH AS1742 AND DIPL STANDARD DRAWINGS. RRPMS AND GUIDEPOSTS MAY ALSO BE REQUIRED IN PROJECT SPECIFIC CIRCUMSTANCES.
- EXTEND PAVEMENT MATERIAL UNDER KERB MINIMUM 75mm THICKNESS AND MINIMUM 300mm BEHIND BACK OF KERB.
- SERVICE CORRIDORS ARE SHOWN ON ONE SIDE OF STREET RESERVE FOR ILLUSTRATION PURPOSES; HOWEVER, THE NOMINATED SERVICE CORRIDORS EXIST ON BOTH SIDES OF THE STREET RESERVE AND ACTUAL SERVICES MAY BE LOCATED ON ONE OR BOTH SIDES OF THE ROAD, AS APPLICABLE.
- PROVIDE 100mm TOPSOIL AND GRASS TO ALL VERGES AND MEDIANS, OR ALTERNATIVE LANDSCAPING TREATMENT.
- REFER PROJECT DRAWINGS FOR EARTHWORKS, SUBGRADE PREPARATION, PAVEMENT MATERIALS AND WEARING SURFACE SPECIFICATIONS.
- FOR STREET NETWORK PLANNING, HIERARCHY SELECTION CRITERIA AND DESIGN BASIS REQUIREMENTS, REFER TO PART 1 SUBDIVISION DEVELOPMENT GUIDELINES.

1	REISSUED AS A STANDARD DRAWING	APR 23	KS	BYRNE
0	ISSUED AS A STANDARD DRAWING	AUG 20	KS	BYRNE
No.	AMENDMENT DESCRIPTION	DATE	INIT.	DEPT/COMPANY

Drawn	KS	Checked	PB
Date:	AUGUST 2020	Date:	AUGUST 2020
Designed	PB	Checked	SPB
Date:	AUGUST 2020	Date:	AUGUST 2020
	Design Project Leader		NTG Project Manager
	SPB		N/A
Date:	AUGUST 2020	Date:	AUGUST 2020



SUBDIVISION DEVELOPMENT GUIDELINES STANDARD DRAWINGS
STREETS AND PATHWAYS

STREET HIERARCHY - CATEGORY A
RESIDENTIAL AND MIXED USE - SET TYPE 2

NTG Project No.	NTG Asset No.	Sheet Reference	NTG Drawing No.	Amendment
-	-	3 OF 4	SS1002	1

Version: March 2021